



Description: ÖLFLEX HEAT 260 GLS 2 X 1,5_

Lapp code: Lapp 0091120

The **Test voltage** of the cable Lapp 0091120 is 1500 V.

Application range

- Extremely high temperatures and mechanical stress require special insulated and armoured cables
- Main applications
 - Ship-building
 - Signal systems
 - Monitoring devices
 - Diesel engines
 - Steam boiler units
 - Turbine manufacturing

Product Make-up

- Fine-wire strand made of nickel-plated copper
- PTFE-based core insulation
- Cores twisted together
- Impregnated glass fibre braiding
- Galvanised steel wire braiding

In our Cable list on next page you can find all interesting information acc. article Lapp 0091120 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 260 GLS					
ÖLFLEX HEAT 260 GLS 2 X 1,5	Lapp 0091120	2 X 1,5	5,7	29.0	93
ÖLFLEX HEAT 260 GLS 3 G 1,5	Lapp 0091121	3 G 1,5	6,1	43.0	102
ÖLFLEX HEAT 260 GLS 4 G 1,5	Lapp 00911223	4 G 1,5	6,6	58.0	130
ÖLFLEX HEAT 260 GLS 5 G 1,5	Lapp 00911233	5 G 1,5	7,3	72.0	149
ÖLFLEX HEAT 260 GLS 7 G 1,5	Lapp 0091124	7 G 1,5	8.0	101.0	180