



Description: ÖLFLEX HEAT 260 MC 2 X 0,5_

Lapp code: Lapp 0091300

The **Test voltage** of the cable Lapp 0091300 is 2500 V.

Application range

- Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
- ÖLFLEX® HEAT 260 has proven to be an effective solution in harsh environments such as paint shop lines
- Typical fields of application
 - Industrial furnace construction
 - Foundries
 - Chemical industry
 - Power plant engineering
 - Paint shop line technology
 - Heating elements
 - Polymer processing
 - Wind turbine engineering

Product Make-up

- Fine-wire strand made of nickel-plated copper
- PTFE-based core insulation
- Cores twisted together
- PTFE-based outer sheath, black

In our Cable list on next page you can find all interesting information acc. article Lapp 0091300 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 260 MC					
ÖLFLEX HEAT 260 MC 2 X 0,5	Lapp 0091300	2 X 0,5	3,9	9.6	22
ÖLFLEX HEAT 260 MC 3 G 0,5	Lapp 0091301	3 G 0,5	4,1	14.4	33
ÖLFLEX HEAT 260 MC 4 G 0,5	Lapp 0091302	4 G 0,5	4,5	19.2	45
ÖLFLEX HEAT 260 MC 2 X 0,75	Lapp 0091305	2 X 0,75	4,2	14.4	32
ÖLFLEX HEAT 260 MC 3 G 0,75	Lapp 0091306	3 G 0,75	4,4	21.6	47
ÖLFLEX HEAT 260 MC 4 G 0,75	Lapp 0091307	4 G 0,75	5,1	28.8	58
ÖLFLEX HEAT 260 MC 2 X 1	Lapp 0091310	2 X 1	4,8	19.2	42
ÖLFLEX HEAT 260 MC 3 G 1	Lapp 0091311	3 G 1	5,1	28.8	56
ÖLFLEX HEAT 260 MC 4 G 1	Lapp 0091312	4 G 1	5,8	38.4	71
ÖLFLEX HEAT 260 MC 3 G 1,5	Lapp 0091315	3 G 1,5	5,6	43.2	72
ÖLFLEX HEAT 260 MC 4 G 1,5	Lapp 0091316	4 G 1,5	6,1	57.6	98
ÖLFLEX HEAT 260 MC 5 G 1,5	Lapp 0091317	5 G 1,5	7.0	72.0	118
ÖLFLEX HEAT 260 MC 3 G 2,5	Lapp 0091320	3 G 2,5	7,1	72.0	87
ÖLFLEX HEAT 260 MC 4 G 2,5	Lapp 0091321	4 G 2,5	7,7	96.0	116
ÖLFLEX HEAT 260 MC 5 G 2,5	Lapp 0091322	5 G 2,5	8,5	120.0	145