



Description: ÖLFLEX HEAT 260 MC 4 G 0,75_

Lapp code: Lapp 0091307

The **Test voltage** of the cable Lapp 0091307 is 2500 V.

Application range

- Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
- ÖLFLEX® HEAT 260 has proven to be an effective solution in harsh environments such as paint shop lines
- Typical fields of application
 - Industrial furnace construction
 - Foundries
 - Chemical industry
 - Power plant engineering
 - Paint shop line technology
 - Heating elements
 - Polymer processing
 - Wind turbine engineering

Product Make-up

- Fine-wire strand made of nickel-plated copper
- PTFE-based core insulation
- Cores twisted together
- PTFE-based outer sheath, black

In our Cable list on next page you can find all interesting information acc. article Lapp 0091307 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® HEAT 260 MC | | | | | |
| ÖLFLEX HEAT 260 MC 2 X 0,5 | Lapp 0091300 | 2 X 0,5 | 3,9 | 9.6 | 22 |
| ÖLFLEX HEAT 260 MC 3 G 0,5 | Lapp 0091301 | 3 G 0,5 | 4,1 | 14.4 | 33 |
| ÖLFLEX HEAT 260 MC 4 G 0,5 | Lapp 0091302 | 4 G 0,5 | 4,5 | 19.2 | 45 |
| ÖLFLEX HEAT 260 MC 2 X 0,75 | Lapp 0091305 | 2 X 0,75 | 4,2 | 14.4 | 32 |
| ÖLFLEX HEAT 260 MC 3 G 0,75 | Lapp 0091306 | 3 G 0,75 | 4,4 | 21.6 | 47 |
| ÖLFLEX HEAT 260 MC 4 G 0,75 | Lapp 0091307 | 4 G 0,75 | 5,1 | 28.8 | 58 |
| ÖLFLEX HEAT 260 MC 2 X 1 | Lapp 0091310 | 2 X 1 | 4,8 | 19.2 | 42 |
| ÖLFLEX HEAT 260 MC 3 G 1 | Lapp 0091311 | 3 G 1 | 5,1 | 28.8 | 56 |
| ÖLFLEX HEAT 260 MC 4 G 1 | Lapp 0091312 | 4 G 1 | 5,8 | 38.4 | 71 |
| ÖLFLEX HEAT 260 MC 3 G 1,5 | Lapp 0091315 | 3 G 1,5 | 5,6 | 43.2 | 72 |
| ÖLFLEX HEAT 260 MC 4 G 1,5 | Lapp 0091316 | 4 G 1,5 | 6,1 | 57.6 | 98 |
| ÖLFLEX HEAT 260 MC 5 G 1,5 | Lapp 0091317 | 5 G 1,5 | 7.0 | 72.0 | 118 |
| ÖLFLEX HEAT 260 MC 3 G 2,5 | Lapp 0091320 | 3 G 2,5 | 7,1 | 72.0 | 87 |
| ÖLFLEX HEAT 260 MC 4 G 2,5 | Lapp 0091321 | 4 G 2,5 | 7,7 | 96.0 | 116 |
| ÖLFLEX HEAT 260 MC 5 G 2,5 | Lapp 0091322 | 5 G 2,5 | 8,5 | 120.0 | 145 |