



Description: ÖLFLEX HEAT 350 MC 3 G 1_

Lapp code: Lapp 0091376

The **Test voltage** of the cable Lapp 0091376 is 1500 V.

Application range

- Wide operating temperature range allows the product to be used in applications under Thermal Class C.
- Blast furnaces and glassworks
- Chemical and power station construction
- Motor and furnace construction
- Lighting, apparatus and instrument industry

Product Make-up

- Fine-wire strand made of nickel-plated copper
- Core insulation: glass fibre covering and impregnated glass fibre braids
- Cores twisted together
- Outer sheath: impregnated glass fibre braiding, white (natural)

In our Cable list on next page you can find all interesting information acc. article Lapp 0091376 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® HEAT 350 MC | | | | | |
| ÖLFLEX HEAT 350 MC 2 X 1 | Lapp 0091375 | 2 X 1 | 6,8 | 19.2 | 56 |
| ÖLFLEX HEAT 350 MC 3 G 1 | Lapp 0091376 | 3 G 1 | 7,4 | 28.8 | 70 |
| ÖLFLEX HEAT 350 MC 4 G 1 | Lapp 0091377 | 4 G 1 | 8,2 | 38.4 | 88 |
| ÖLFLEX HEAT 350 MC 2 X 1,5 | Lapp 0091380 | 2 X 1,5 | 7,8 | 28.8 | 77 |
| ÖLFLEX HEAT 350 MC 3 G 1,5 | Lapp 0091381 | 3 G 1,5 | 8,4 | 43.2 | 93 |
| ÖLFLEX HEAT 350 MC 4 G 1,5 | Lapp 0091382 | 4 G 1,5 | 9,4 | 57.6 | 118 |
| ÖLFLEX HEAT 350 MC 5 G 1,5 | Lapp 0091383 | 5 G 1,5 | 10,3 | 72.0 | 140 |
| ÖLFLEX HEAT 350 MC 3 G 2,5 | Lapp 0091390 | 3 G 2,5 | 8,9 | 72.0 | 124 |
| ÖLFLEX HEAT 350 MC 4 G 2,5 | Lapp 0091391 | 4 G 2,5 | 9,8 | 96.0 | 160 |
| ÖLFLEX HEAT 350 MC 5 G 2,5 | Lapp 0091392 | 5 G 2,5 | 10,1 | 120.0 | 194 |