



Description: ÖLFLEX HEAT 350 MC 5 G 2,5_

Lapp code: Lapp 0091392

The **Test voltage** of the cable Lapp 0091392 is 1500 V.

Application range

- Wide operating temperature range allows the product to be used in applications under Thermal Class C.
- Blast furnaces and glassworks
- Chemical and power station construction
- Motor and furnace construction
- Lighting, apparatus and instrument industry

Product Make-up

- Fine-wire strand made of nickel-plated copper
- Core insulation: glass fibre covering and impregnated glass fibre braids
- Cores twisted together
- Outer sheath: impregnated glass fibre braiding, white (natural)

In our Cable list on next page you can find all interesting information acc. article Lapp 0091392 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 350 MC					
ÖLFLEX HEAT 350 MC 2 X 1	Lapp 0091375	2 X 1	6,8	19.2	56
ÖLFLEX HEAT 350 MC 3 G 1	Lapp 0091376	3 G 1	7,4	28.8	70
ÖLFLEX HEAT 350 MC 4 G 1	Lapp 0091377	4 G 1	8,2	38.4	88
ÖLFLEX HEAT 350 MC 2 X 1,5	Lapp 0091380	2 X 1,5	7,8	28.8	77
ÖLFLEX HEAT 350 MC 3 G 1,5	Lapp 0091381	3 G 1,5	8,4	43.2	93
ÖLFLEX HEAT 350 MC 4 G 1,5	Lapp 0091382	4 G 1,5	9,4	57.6	118
ÖLFLEX HEAT 350 MC 5 G 1,5	Lapp 0091383	5 G 1,5	10,3	72.0	140
ÖLFLEX HEAT 350 MC 3 G 2,5	Lapp 0091390	3 G 2,5	8,9	72.0	124
ÖLFLEX HEAT 350 MC 4 G 2,5	Lapp 0091391	4 G 2,5	9,8	96.0	160
ÖLFLEX HEAT 350 MC 5 G 2,5	Lapp 0091392	5 G 2,5	10,1	120.0	194