

Description: ÖLFLEX HEAT 350 SC 0,75_

Lapp code: Lapp 0091351

The **Test voltage** of the cable Lapp 0091351 is 1500 V.

Application range

- Wide operating temperature range allows the product to be used in applications under Thermal Class C.
- Blast furnaces and glassworks
- Chemical and power station construction
- Motor and furnace construction
- Lighting, apparatus and instrument industry

Product Make-up

- Fine-wire strand made of nickel-plated copper
- Core insulation: glass fibre covering (additional mica wrapping from 16 mm²) and impregnated glass fibre braid, core colour = white (natural)

In our Cable list on next page you can find all interesting information acc. article Lapp 0091351 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 350 SC					
ÖLFLEX HEAT 350 SC 0,5	Lapp 0091350	0,5	2,5	4.8	13.0
ÖLFLEX HEAT 350 SC 0,75	Lapp 0091351	0,75	3.0	7.2	15.0
ÖLFLEX HEAT 350 SC 1	Lapp 0091352	1	3,4	9.6	17.0
ÖLFLEX HEAT 350 SC 1,5	Lapp 0091353	1,5	3,5	14.4	23.0
ÖLFLEX HEAT 350 SC 2,5	Lapp 0091354	2,5	3,7	24.0	34.0
ÖLFLEX HEAT 350 SC 4	Lapp 0091355	4	4,2	38.4	54.0
ÖLFLEX HEAT 350 SC 6	Lapp 0091356	6	6,2	57.6	84.0
ÖLFLEX HEAT 350 SC 10	Lapp 0091357	10	7,3	96.0	120.0
ÖLFLEX HEAT 350 SC 16	Lapp 0091358	16	8.0	153.6	199.0
ÖLFLEX HEAT 350 SC 25	Lapp 0091359	25	9,5	240.0	300.0
ÖLFLEX HEAT 350 SC 35	Lapp 0091360	35	10,9	336.0	399.0
ÖLFLEX HEAT 350 SC 50	Lapp 0091361	50	13,2	480.0	540.0