



Description: ÖLFLEX HEAT 350 SC 16_

Lapp code: Lapp 0091358

The **Test voltage** of the cable Lapp 0091358 is 1500 V.

Application range

- Wide operating temperature range allows the product to be used in applications under Thermal Class C.
- Blast furnaces and glassworks
- Chemical and power station construction
- Motor and furnace construction
- Lighting, apparatus and instrument industry

Product Make-up

- Fine-wire strand made of nickel-plated copper
- Core insulation: glass fibre covering (additional mica wrapping from 16 mm²) and impregnated glass fibre braid, core colour = white (natural)

In our Cable list on next page you can find all interesting information acc. article Lapp 0091358 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Conductor cross-section (mm ²) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|--------------|--|---------------------|----------------------|----------------|
| ÖLFLEX® HEAT 350 SC | | | | | |
| ÖLFLEX HEAT 350 SC 0,5 | Lapp 0091350 | 0,5 | 2,5 | 4.8 | 13.0 |
| ÖLFLEX HEAT 350 SC 0,75 | Lapp 0091351 | 0,75 | 3.0 | 7.2 | 15.0 |
| ÖLFLEX HEAT 350 SC 1 | Lapp 0091352 | 1 | 3,4 | 9.6 | 17.0 |
| ÖLFLEX HEAT 350 SC 1,5 | Lapp 0091353 | 1,5 | 3,5 | 14.4 | 23.0 |
| ÖLFLEX HEAT 350 SC 2,5 | Lapp 0091354 | 2,5 | 3,7 | 24.0 | 34.0 |
| ÖLFLEX HEAT 350 SC 4 | Lapp 0091355 | 4 | 4,2 | 38.4 | 54.0 |
| ÖLFLEX HEAT 350 SC 6 | Lapp 0091356 | 6 | 6,2 | 57.6 | 84.0 |
| ÖLFLEX HEAT 350 SC 10 | Lapp 0091357 | 10 | 7,3 | 96.0 | 120.0 |
| ÖLFLEX HEAT 350 SC 16 | Lapp 0091358 | 16 | 8.0 | 153.6 | 199.0 |
| ÖLFLEX HEAT 350 SC 25 | Lapp 0091359 | 25 | 9,5 | 240.0 | 300.0 |
| ÖLFLEX HEAT 350 SC 35 | Lapp 0091360 | 35 | 10,9 | 336.0 | 399.0 |
| ÖLFLEX HEAT 350 SC 50 | Lapp 0091361 | 50 | 13,2 | 480.0 | 540.0 |