



Description: ÖLFLEX LIFT 12 G 1,0_

Lapp code: Lapp 0027022

The **Test voltage** of the cable Lapp 0027022 is 4000 V.

Application range

- Lift cable that ensures the electrical integrity in various areas of lift construction
- Suitable for use in outdoor lifts
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX(R) LIFT cables please see the catalogue appendix, technical table T5

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Supporting element made of hemp or aramid
- Fleece-wrapping between cores and sheath
- Special PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 0027022 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Max. suspension length (m)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® LIFT						
ÖLFLEX LIFT 7 G 1,0	Lapp 0027020	7 G 1,0	11.5	80	67.2	178
ÖLFLEX LIFT 12 G 1,0	Lapp 0027022	12 G 1,0	16.3	80	115.2	332
ÖLFLEX LIFT 18 G 1,0	Lapp 0027024	18 G 1,0	16.4	70	172.8	405
ÖLFLEX LIFT 24 G 1,0	Lapp 0027027	24 G 1,0	19.4	60	230.4	533.25
ÖLFLEX LIFT 36 G 1,0	Lapp 0027029	36 G 1,0	25.1	90	345.6	887