



Description: ÖLFLEX LIFT S 24 G 1,0_

Lapp code: Lapp 0027009

The **Test voltage** of the cable Lapp 0027009 is 4000 V.

Application range

- Lift cable that ensures the electrical integrity in various areas of lift construction
- Suitable for use in outdoor lifts
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX(R) LIFT cables please see the catalogue appendix, technical table T5

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Steel support element
- Fleece-wrapping between cores and sheath
- Support braid made of textile fibre blend
- Special PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 0027009 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Max. suspension length (m)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® LIFT S						
ÖLFLEX LIFT S 24 G 1,0	Lapp 0027009	24 G 1,0	22.1	150	230.0	680
ÖLFLEX LIFT S 36 G 1,0	Lapp 0027010	36 G 1,0	28.6	150	345.6	1092