



Description: ÖLFLEX LIFT T 12 G 1,0_

Lapp code: Lapp 0027002

The **Test voltage** of the cable Lapp 0027002 is 4000 V.

Application range

- Lift cable that ensures the electrical integrity in various areas of lift construction
- Suitable for use in outdoor lifts
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX(R) LIFT cables please see the catalogue appendix, technical table T5

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Supporting element made of hemp or aramid
- Fleece-wrapping between cores and sheath
- Support braid made of textile fibre blend
- Special PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 0027002 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Max. suspension length (m)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® LIFT T						
ÖLFLEX LIFT T 12 G 0,75	Lapp 0027506	12 G 0,75	18.1	110	86.0	360
ÖLFLEX LIFT T 18 G 0,75	Lapp 0027507	18 G 0,75	18.3	110	129.6	460
ÖLFLEX LIFT T 24 G 0,75	Lapp 0027508	24 G 0,75	21.0	80	172.8	530
ÖLFLEX LIFT T 7 G 1,0	Lapp 0027001	7 G 1,0	14.5	80	67.0	225
ÖLFLEX LIFT T 12 G 1,0	Lapp 0027002	12 G 1,0	19.2	80	115.0	410
ÖLFLEX LIFT T 18 G 1,0	Lapp 0027008	18 G 1,0	19.5	70	172.8	475
ÖLFLEX LIFT T 20 G 1,0	Lapp 0027004	20 G 1,0	20.3	70	192.0	525
ÖLFLEX LIFT T 24 G 1,0	Lapp 0027005	24 G 1,0	22.1	60	230.0	600
ÖLFLEX LIFT T 36 G 1,0	Lapp 0027007	36 G 1,0	28.6	90	345.6	950
ÖLFLEX LIFT T 28 G 1,0 + 2 x (0,5) C	Lapp 0027006	28 G 1,0 + 2 x (0,5) C	25.2	90	293.0	765