



Description: ÖLFLEX PLUG 540 P Connection Cable 3 G 1,5_

Lapp code: Lapp 73220850

The **Test voltage** of the cable Lapp 73220850 is Assembly: 2000 V ÖLFLEX® 540 P: 3000 V.

Application range

- Harsh conditions
- Mechanical engineering
- Construction industry
- Medical equipment
- In damp interiors or outdoors

Product Make-up

- Strands of tinned-copper wires
- Core insulation: TPE
- Outer sheath made of special polyurethane
- 1st option for DIN/VDE connector with type certification: 2-core ÖLFLEX® 540 P cable in conjunction with straight, extruded, round, shaped, 16 A/250 Vac-to-ground DIN/VDE central 2-pin attachment contour plug (CEE 7/17) without earthed contact according to DIN VDE 0620-1/DIN 49406-R and with plug protection rating IP 20 as well as with non-contacting hole in the overmould for the round earthing pin of the French plug system type E currently applied in France incl. Corsica, Belgium, Czech Republic, Slovakia, Poland, Morocco, Tunisia, ... for example
- 2nd alternative of DIN/ VDE type certified plug: 3-core ÖLFLEX® 540 P cable incl. green-yellow, protective equipment grounding conductor in conjunction with 3-pole, straight, moulded, splash water protected, central, 16A/ 250Vac-to-ground, isolated ground DIN/ VDE hybrid plug (CEE 7/7 combining the French type E with the German "Schuko" type E) incl. double protection/ earthing contact/ pin system according to DIN VDE 0620-1/ DIN 49441-R2/ DIN 49441-2-AR2 as well as with plug protection type/ category IP 44 and with contacting hole for the round earthing pin of the French plug system type E currently applied in France incl. Corsica, Belgium, Czech Republic, Slovakia, Poland, Morocco, Tunisia, ... for example
- Other end: 30 mm dismantled, with protection sleeves for the ends of the conductor
- Other, international plug versions in conjunction with the cable ÖLFLEX® 540 P on request, for example for Switzerland, Australia, China, Denmark, Italy, United Kingdom, etc....

In our Cable list on next page you can find all interesting information acc. article Lapp 73220850 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Charging current	Outer diameter (mm)	Length (m)	Copper index kg/1.000 pieces
#####					
ÖLFLEX PLUG 540 P Connection Cable 2 X 1	Lapp 73220842	2 X 1	7.0	2.0	38.4
ÖLFLEX PLUG 540 P Connection Cable 2 X 1	Lapp 73220843	2 X 1	7.0	3.5	67.2
ÖLFLEX PLUG 540 P Connection Cable 2 X 1	Lapp 73220844	2 X 1	7.0	5.0	96.0
ÖLFLEX PLUG 540 P Connection Cable 2 X 1,5	Lapp 73221558	2 X 1,5	8,4	2.0	57.6
ÖLFLEX PLUG 540 P Connection Cable 2 X 1,5	Lapp 73221559	2 X 1,5	8,4	3.5	86.4
ÖLFLEX PLUG 540 P Connection Cable 2 X 1,5	Lapp 73221560	2 X 1,5	8,4	5.0	144.0
#####					
ÖLFLEX PLUG 540 P Connection Cable 3 G 0,75	Lapp 73220846	3 G 0,75	7.0	2.0	43.2
ÖLFLEX PLUG 540 P Connection Cable 3 G 0,75	Lapp 73220847	3 G 0,75	7.0	3.5	75.6
ÖLFLEX PLUG 540 P Connection Cable 3 G 0,75	Lapp 73220848	3 G 0,75	7.0	5.0	108.0
ÖLFLEX PLUG 540 P Connection Cable 3 G 1	Lapp 73221561	3 G 1	7,4	2.0	57.6
ÖLFLEX PLUG 540 P Connection Cable 3 G 1	Lapp 73221562	3 G 1	7,4	3.5	100.8
ÖLFLEX PLUG 540 P Connection Cable 3 G 1	Lapp 73221563	3 G 1	7,4	5.0	144.0
ÖLFLEX PLUG 540 P Connection Cable 3 G 1,5	Lapp 73220849	3 G 1,5	8,9	2.0	86.0
ÖLFLEX PLUG 540 P Connection Cable 3 G 1,5	Lapp 73220850	3 G 1,5	8,9	3.5	150.6
ÖLFLEX PLUG 540 P Connection Cable 3 G 1,5	Lapp 73220851	3 G 1,5	8,9	5.0	215.0