



Description: ÖLFLEX ROBUST 200 3 G 4_

Lapp code: Lapp 0021816

The **Test voltage** of the cable Lapp 0021816 is 4000 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Outer sheath made of special TPE
- Sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 0021816 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® ROBUST 200					
ÖLFLEX ROBUST 200 2 X 1,0	Lapp 0021800	2 X 1,0	8,0	19,2	65
ÖLFLEX ROBUST 200 3 G 1,0	Lapp 0021801	3 G 1,0	8,4	29,0	79
ÖLFLEX ROBUST 200 4 G 1,0	Lapp 0021802	4 G 1,0	9,2	38,4	96
ÖLFLEX ROBUST 200 5 G 1,0	Lapp 0021803	5 G 1,0	10,0	48,0	113
ÖLFLEX ROBUST 200 2 X 1,5	Lapp 0021805	2 X 1,5	8,6	29,0	78
ÖLFLEX ROBUST 200 3 G 1,5	Lapp 0021806	3 G 1,5	9,1	43,0	97
ÖLFLEX ROBUST 200 4 G 1,5	Lapp 0021807	4 G 1,5	9,9	58,0	122
ÖLFLEX ROBUST 200 5 G 1,5	Lapp 0021808	5 G 1,5	10,8	72,0	146
ÖLFLEX ROBUST 200 7 G 1,5	Lapp 0021809	7 G 1,5	13,5	101,0	208
ÖLFLEX ROBUST 200 2 X 2,5	Lapp 0021810	2 X 2,5	9,8	48,0	114
ÖLFLEX ROBUST 200 3 G 2,5	Lapp 0021811	3 G 2,5	10,4	72,0	144
ÖLFLEX ROBUST 200 4 G 2,5	Lapp 0021812	4 G 2,5	11,5	96,0	181
ÖLFLEX ROBUST 200 5 G 2,5	Lapp 0021813	5 G 2,5	13,1	120,0	222
ÖLFLEX ROBUST 200 7 G 2,5	Lapp 0021814	7 G 2,5	15,9	168,0	312
ÖLFLEX ROBUST 200 3 G 4	Lapp 0021816	3 G 4	12,4	115,2	215
ÖLFLEX ROBUST 200 4 G 4	Lapp 0021817	4 G 4	14,0	154,0	273
ÖLFLEX ROBUST 200 5 G 4	Lapp 0021818	5 G 4	15,8	192,0	333
ÖLFLEX ROBUST 200 4 G 6	Lapp 0021822	4 G 6	15,7	230,0	378
ÖLFLEX ROBUST 200 5 G 6	Lapp 0021823	5 G 6	17,2	288,0	463
ÖLFLEX ROBUST 200 4 G 10	Lapp 0021825	4 G 10	19,4	384,0	570
ÖLFLEX ROBUST 200 5 G 10	Lapp 0021826	5 G 10	21,4	480,0	770
ÖLFLEX ROBUST 200 4 G 16	Lapp 0021828	4 G 16	22,4	614,0	885
ÖLFLEX ROBUST 200 5 G 16	Lapp 0021829	5 G 16	24,6	768,0	1100
ÖLFLEX ROBUST 200 4 G 25	Lapp 0021831	4 G 25	27,0	960,0	1365

ÖLFLEX ROBUST 200 3 G 4_

Lapp 0021816



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX ROBUST 200 4 G 35	Lapp 0021833	4 G 35	29,7	1344.0	1773
ÖLFLEX ROBUST 200 4 G 50	Lapp 0021836	4 G 50	36,2	1920.0	3454