



Description: ÖLFLEX ROBUST 200 5 G 16_

Lapp code: Lapp 0021829

The **Test voltage** of the cable Lapp 0021829 is 4000 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Outer sheath made of special TPE
- Sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 0021829 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® ROBUST 200 | | | | | |
| ÖLFLEX ROBUST 200 2 X 1,0 | Lapp 0021800 | 2 X 1,0 | 8,0 | 19,2 | 65 |
| ÖLFLEX ROBUST 200 3 G 1,0 | Lapp 0021801 | 3 G 1,0 | 8,4 | 29,0 | 79 |
| ÖLFLEX ROBUST 200 4 G 1,0 | Lapp 0021802 | 4 G 1,0 | 9,2 | 38,4 | 96 |
| ÖLFLEX ROBUST 200 5 G 1,0 | Lapp 0021803 | 5 G 1,0 | 10,0 | 48,0 | 113 |
| ÖLFLEX ROBUST 200 2 X 1,5 | Lapp 0021805 | 2 X 1,5 | 8,6 | 29,0 | 78 |
| ÖLFLEX ROBUST 200 3 G 1,5 | Lapp 0021806 | 3 G 1,5 | 9,1 | 43,0 | 97 |
| ÖLFLEX ROBUST 200 4 G 1,5 | Lapp 0021807 | 4 G 1,5 | 9,9 | 58,0 | 122 |
| ÖLFLEX ROBUST 200 5 G 1,5 | Lapp 0021808 | 5 G 1,5 | 10,8 | 72,0 | 146 |
| ÖLFLEX ROBUST 200 7 G 1,5 | Lapp 0021809 | 7 G 1,5 | 13,5 | 101,0 | 208 |
| ÖLFLEX ROBUST 200 2 X 2,5 | Lapp 0021810 | 2 X 2,5 | 9,8 | 48,0 | 114 |
| ÖLFLEX ROBUST 200 3 G 2,5 | Lapp 0021811 | 3 G 2,5 | 10,4 | 72,0 | 144 |
| ÖLFLEX ROBUST 200 4 G 2,5 | Lapp 0021812 | 4 G 2,5 | 11,5 | 96,0 | 181 |
| ÖLFLEX ROBUST 200 5 G 2,5 | Lapp 0021813 | 5 G 2,5 | 13,1 | 120,0 | 222 |
| ÖLFLEX ROBUST 200 7 G 2,5 | Lapp 0021814 | 7 G 2,5 | 15,9 | 168,0 | 312 |
| ÖLFLEX ROBUST 200 3 G 4 | Lapp 0021816 | 3 G 4 | 12,4 | 115,2 | 215 |
| ÖLFLEX ROBUST 200 4 G 4 | Lapp 0021817 | 4 G 4 | 14,0 | 154,0 | 273 |
| ÖLFLEX ROBUST 200 5 G 4 | Lapp 0021818 | 5 G 4 | 15,8 | 192,0 | 333 |
| ÖLFLEX ROBUST 200 4 G 6 | Lapp 0021822 | 4 G 6 | 15,7 | 230,0 | 378 |
| ÖLFLEX ROBUST 200 5 G 6 | Lapp 0021823 | 5 G 6 | 17,2 | 288,0 | 463 |
| ÖLFLEX ROBUST 200 4 G 10 | Lapp 0021825 | 4 G 10 | 19,4 | 384,0 | 570 |
| ÖLFLEX ROBUST 200 5 G 10 | Lapp 0021826 | 5 G 10 | 21,4 | 480,0 | 770 |
| ÖLFLEX ROBUST 200 4 G 16 | Lapp 0021828 | 4 G 16 | 22,4 | 614,0 | 885 |
| ÖLFLEX ROBUST 200 5 G 16 | Lapp 0021829 | 5 G 16 | 24,6 | 768,0 | 1100 |
| ÖLFLEX ROBUST 200 4 G 25 | Lapp 0021831 | 4 G 25 | 27,0 | 960,0 | 1365 |

ÖLFLEX ROBUST 200 5 G 16_

Lapp 0021829



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX ROBUST 200 4 G 35 | Lapp 0021833 | 4 G 35 | 29,7 | 1344.0 | 1773 |
| ÖLFLEX ROBUST 200 4 G 50 | Lapp 0021836 | 4 G 50 | 36,2 | 1920.0 | 3454 |