



**Description:** ÖLFLEX ROBUST 200 7 G 1,5\_

**Lapp code:** Lapp 0021809

The **Test voltage** of the cable Lapp 0021809 is 4000 V.

## Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Outer sheath made of special TPE
- Sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 0021809 and much more.

CABLE LIST - all informations you need you can find here

| Product Name              | Lapp Nr.     | Number of cores and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® ROBUST 200        |              |   |                     |                      |                |
| ÖLFLEX ROBUST 200 2 X 1,0 | Lapp 0021800 | 2 X 1,0   | 8,0                 | 19,2                 | 65             |
| ÖLFLEX ROBUST 200 3 G 1,0 | Lapp 0021801 | 3 G 1,0   | 8,4                 | 29,0                 | 79             |
| ÖLFLEX ROBUST 200 4 G 1,0 | Lapp 0021802 | 4 G 1,0   | 9,2                 | 38,4                 | 96             |
| ÖLFLEX ROBUST 200 5 G 1,0 | Lapp 0021803 | 5 G 1,0   | 10,0                | 48,0                 | 113            |
| ÖLFLEX ROBUST 200 2 X 1,5 | Lapp 0021805 | 2 X 1,5   | 8,6                 | 29,0                 | 78             |
| ÖLFLEX ROBUST 200 3 G 1,5 | Lapp 0021806 | 3 G 1,5   | 9,1                 | 43,0                 | 97             |
| ÖLFLEX ROBUST 200 4 G 1,5 | Lapp 0021807 | 4 G 1,5   | 9,9                 | 58,0                 | 122            |
| ÖLFLEX ROBUST 200 5 G 1,5 | Lapp 0021808 | 5 G 1,5   | 10,8                | 72,0                 | 146            |
| ÖLFLEX ROBUST 200 7 G 1,5 | Lapp 0021809 | 7 G 1,5   | 13,5                | 101,0                | 208            |
| ÖLFLEX ROBUST 200 2 X 2,5 | Lapp 0021810 | 2 X 2,5   | 9,8                 | 48,0                 | 114            |
| ÖLFLEX ROBUST 200 3 G 2,5 | Lapp 0021811 | 3 G 2,5   | 10,4                | 72,0                 | 144            |
| ÖLFLEX ROBUST 200 4 G 2,5 | Lapp 0021812 | 4 G 2,5   | 11,5                | 96,0                 | 181            |
| ÖLFLEX ROBUST 200 5 G 2,5 | Lapp 0021813 | 5 G 2,5   | 13,1                | 120,0                | 222            |
| ÖLFLEX ROBUST 200 7 G 2,5 | Lapp 0021814 | 7 G 2,5   | 15,9                | 168,0                | 312            |
| ÖLFLEX ROBUST 200 3 G 4   | Lapp 0021816 | 3 G 4   | 12,4                | 115,2                | 215            |
| ÖLFLEX ROBUST 200 4 G 4   | Lapp 0021817 | 4 G 4   | 14,0                | 154,0                | 273            |
| ÖLFLEX ROBUST 200 5 G 4   | Lapp 0021818 | 5 G 4   | 15,8                | 192,0                | 333            |
| ÖLFLEX ROBUST 200 4 G 6   | Lapp 0021822 | 4 G 6   | 15,7                | 230,0                | 378            |
| ÖLFLEX ROBUST 200 5 G 6   | Lapp 0021823 | 5 G 6   | 17,2                | 288,0                | 463            |
| ÖLFLEX ROBUST 200 4 G 10  | Lapp 0021825 | 4 G 10  | 19,4                | 384,0                | 570            |
| ÖLFLEX ROBUST 200 5 G 10  | Lapp 0021826 | 5 G 10  | 21,4                | 480,0                | 770            |
| ÖLFLEX ROBUST 200 4 G 16  | Lapp 0021828 | 4 G 16  | 22,4                | 614,0                | 885            |
| ÖLFLEX ROBUST 200 5 G 16  | Lapp 0021829 | 5 G 16  | 24,6                | 768,0                | 1100           |
| ÖLFLEX ROBUST 200 4 G 25  | Lapp 0021831 | 4 G 25  | 27,0                | 960,0                | 1365           |

# ÖLFLEX ROBUST 200 7 G 1,5\_

Lapp 0021809



| Product Name                | Lapp Nr.     | Number of cores and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX ROBUST 200<br>4 G 35 | Lapp 0021833 | 4 G 35  | 29,7                | 1344.0               | 1773           |
| ÖLFLEX ROBUST 200<br>4 G 50 | Lapp 0021836 | 4 G 50  | 36,2                | 1920.0               | 3454           |