



Description: ÖLFLEX ROBUST 215 C 25 G 0,5_

Lapp code: Lapp 0022713

The **Test voltage** of the cable Lapp 0022713 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use
- In EMC-sensitive environments (electromagnetic compatibility)

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Halogen-free plastic foil wrapping
- Tinned copper screen braiding
- Outer sheath made of special TPE
- Sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 0022713 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® ROBUST 215 C | | | | | |
| ÖLFLEX ROBUST 215 C 2 X 0,5 | Lapp 0022700 | 2 X 0,5 | 5,9 | 36.0 | 42 |
| ÖLFLEX ROBUST 215 C 3 G 0,5 | Lapp 0022701 | 3 G 0,5 | 6,2 | 43.0 | 52 |
| ÖLFLEX ROBUST 215 C 3 X 0,5 | Lapp 0022702 | 3 X 0,5 | 6,2 | 43.0 | 52 |
| ÖLFLEX ROBUST 215 C 4 G 0,5 | Lapp 0022703 | 4 G 0,5 | 6,6 | 49.0 | 59 |
| ÖLFLEX ROBUST 215 C 4 X 0,5 | Lapp 0022704 | 4 X 0,5 | 6,6 | 49.0 | 59 |
| ÖLFLEX ROBUST 215 C 5 G 0,5 | Lapp 0022705 | 5 G 0,5 | 7,1 | 57.0 | 68 |
| ÖLFLEX ROBUST 215 C 5 X 0,5 | Lapp 0022706 | 5 X 0,5 | 7,1 | 57.0 | 68 |
| ÖLFLEX ROBUST 215 C 7 G 0,5 | Lapp 0022708 | 7 G 0,5 | 7,7 | 69.0 | 85 |
| ÖLFLEX ROBUST 215 C 7 X 0,5 | Lapp 0022709 | 7 X 0,5 | 7,7 | 69.0 | 85 |
| ÖLFLEX ROBUST 215 C 12 G 0,5 | Lapp 0022711 | 12 G 0,5 | 10,1 | 104.0 | 136 |
| ÖLFLEX ROBUST 215 C 18 G 0,5 | Lapp 0022712 | 18 G 0,5 | 11,8 | 141.0 | 189 |
| ÖLFLEX ROBUST 215 C 25 G 0,5 | Lapp 0022713 | 25 G 0,5 | 13,7 | 211.0 | 265 |
| ÖLFLEX ROBUST 215 C 2 X 0,75 | Lapp 0022717 | 2 X 0,75 | 6,3 | 43.0 | 50 |
| ÖLFLEX ROBUST 215 C 3 G 0,75 | Lapp 0022718 | 3 G 0,75 | 6,6 | 52.0 | 60 |
| ÖLFLEX ROBUST 215 C 3 X 0,75 | Lapp 0022719 | 3 X 0,75 | 6,6 | 52.0 | 60 |
| ÖLFLEX ROBUST 215 C 4 G 0,75 | Lapp 0022720 | 4 G 0,75 | 7,1 | 61.0 | 72 |
| ÖLFLEX ROBUST 215 C 4 X 0,75 | Lapp 0022721 | 4 X 0,75 | 7,1 | 61.0 | 72 |
| ÖLFLEX ROBUST 215 C 5 G 0,75 | Lapp 0022722 | 5 G 0,75 | 7,9 | 72.0 | 88 |
| ÖLFLEX ROBUST 215 C 5 X 0,75 | Lapp 0022723 | 5 X 0,75 | 7,9 | 72.0 | 88 |
| ÖLFLEX ROBUST 215 C 7 G 0,75 | Lapp 0022724 | 7 G 0,75 | 8,5 | 89.0 | 110 |
| ÖLFLEX ROBUST 215 C 7 X 0,75 | Lapp 0022725 | 7 X 0,75 | 8,5 | 89.0 | 110 |
| ÖLFLEX ROBUST 215 C 12 G 0,75 | Lapp 0022727 | 12 G 0,75 | 11,1 | 138.0 | 177 |
| ÖLFLEX ROBUST 215 C 18 G 0,75 | Lapp 0022728 | 18 G 0,75 | 13.0 | 211.0 | 247 |
| ÖLFLEX ROBUST 215 C 25 G 0,75 | Lapp 0022729 | 25 G 0,75 | 15,1 | 280.0 | 347 |

ÖLFLEX ROBUST 215 C 25 G 0,5_

Lapp 0022713



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX ROBUST 215 C 34 G 0,75 | Lapp 0022730 | 34 G 0,75 | 17,5 | 380.0 | 460 |
| ÖLFLEX ROBUST 215 C 2 X 1,0 | Lapp 0022733 | 2 X 1,0 | 6,6 | 51.0 | 60 |
| ÖLFLEX ROBUST 215 C 3 G 1,0 | Lapp 0022734 | 3 G 1,0 | 6,9 | 62.0 | 70 |
| ÖLFLEX ROBUST 215 C 3 X 1,0 | Lapp 0022735 | 3 X 1,0 | 6,9 | 62.0 | 70 |
| ÖLFLEX ROBUST 215 C 4 G 1,0 | Lapp 0022736 | 4 G 1,0 | 7,4 | 74.0 | 85 |
| ÖLFLEX ROBUST 215 C 4 X 1,0 | Lapp 0022737 | 4 X 1,0 | 7,4 | 74.0 | 85 |
| ÖLFLEX ROBUST 215 C 5 G 1,0 | Lapp 0022738 | 5 G 1,0 | 8,3 | 88.0 | 103 |
| ÖLFLEX ROBUST 215 C 5 X 1,0 | Lapp 0022739 | 5 X 1,0 | 8,3 | 88.0 | 103 |
| ÖLFLEX ROBUST 215 C 7 G 1,0 | Lapp 0022740 | 7 G 1,0 | 8,9 | 112.0 | 131 |
| ÖLFLEX ROBUST 215 C 12 G 1,0 | Lapp 0022742 | 12 G 1,0 | 11,7 | 185.0 | 213 |
| ÖLFLEX ROBUST 215 C 18 G 1,0 | Lapp 0022743 | 18 G 1,0 | 14,1 | 268.0 | 321 |
| ÖLFLEX ROBUST 215 C 25 G 1,0 | Lapp 0022744 | 25 G 1,0 | 16,2 | 354.0 | 425 |
| ÖLFLEX ROBUST 215 C 2 X 1,5 | Lapp 0022748 | 2 X 1,5 | 7,2 | 65.0 | 71 |
| ÖLFLEX ROBUST 215 C 3 G 1,5 | Lapp 0022749 | 3 G 1,5 | 7,6 | 82.0 | 90 |
| ÖLFLEX ROBUST 215 C 3 X 1,5 | Lapp 0022750 | 3 X 1,5 | 7,6 | 82.0 | 90 |
| ÖLFLEX ROBUST 215 C 4 G 1,5 | Lapp 0022751 | 4 G 1,5 | 8,4 | 100.0 | 114 |
| ÖLFLEX ROBUST 215 C 4 X 1,5 | Lapp 0022752 | 4 X 1,5 | 8,4 | 100.0 | 114 |
| ÖLFLEX ROBUST 215 C 5 G 1,5 | Lapp 0022753 | 5 G 1,5 | 9,1 | 119.0 | 136 |
| ÖLFLEX ROBUST 215 C 5 X 1,5 | Lapp 0022754 | 5 X 1,5 | 9,1 | 119.0 | 136 |
| ÖLFLEX ROBUST 215 C 7 G 1,5 | Lapp 0022756 | 7 G 1,5 | 10,0 | 154.0 | 177 |
| ÖLFLEX ROBUST 215 C 7 X 1,5 | Lapp 0022757 | 7 X 1,5 | 10,0 | 154.0 | 177 |
| ÖLFLEX ROBUST 215 C 12 G 1,5 | Lapp 0022760 | 12 G 1,5 | 13,4 | 268.0 | 290 |
| ÖLFLEX ROBUST 215 C 18 G 1,5 | Lapp 0022761 | 18 G 1,5 | 15,8 | 373.0 | 435 |
| ÖLFLEX ROBUST 215 C 25 G 1,5 | Lapp 0022762 | 25 G 1,5 | 18,2 | 530.0 | 579 |
| ÖLFLEX ROBUST 215 C 34 G 1,5 | Lapp 0022763 | 34 G 1,5 | 21,2 | 683.0 | 797 |
| ÖLFLEX ROBUST 215 C 3 G 2,5 | Lapp 0022767 | 3 G 2,5 | 9,1 | 118.0 | 134 |

ÖLFLEX ROBUST 215 C 25 G 0,5_

Lapp 0022713



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX ROBUST 215 C 4 G 2,5 | Lapp 0022768 | 4 G 2,5 | 10,0 | 147,0 | 169 |
| ÖLFLEX ROBUST 215 C 5 G 2,5 | Lapp 0022769 | 5 G 2,5 | 11,1 | 176,0 | 207 |
| ÖLFLEX ROBUST 215 C 7 G 2,5 | Lapp 0022770 | 7 G 2,5 | 12,0 | 253,0 | 270 |
| ÖLFLEX ROBUST 215 C 4 G 4 | Lapp 0022774 | 4 G 4 | 11,9 | 190,0 | 258 |
| ÖLFLEX ROBUST 215 C 4 G 6 | Lapp 0022776 | 4 G 6 | 14,5 | 290,0 | 392 |
| ÖLFLEX ROBUST 215 C 4 G 10 | Lapp 0022777 | 4 G 10 | 17,5 | 458,0 | 602 |
| ÖLFLEX ROBUST 215 C 4 G 16 | Lapp 0022778 | 4 G 16 | 20,2 | 736,6 | 928 |
| ÖLFLEX ROBUST 215 C 4 G 25 | Lapp 0022771 | 4 G 25 | 25,1 | 1126,7 | 1411 |
| ÖLFLEX ROBUST 215 C 4 G 35 | Lapp 0022780 | 4 G 35 | 28,0 | 1540,0 | 1883 |