



Description: ÖLFLEX ROBUST 215 C 7 X 0,75_

Lapp code: Lapp 0022725

The **Test voltage** of the cable Lapp 0022725 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use
- In EMC-sensitive environments (electromagnetic compatibility)

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Halogen-free plastic foil wrapping
- Tinned copper screen braiding
- Outer sheath made of special TPE
- Sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 0022725 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® ROBUST 215 C					
ÖLFLEX ROBUST 215 C 2 X 0,5	Lapp 0022700	2 X 0,5	5,9	36.0	42
ÖLFLEX ROBUST 215 C 3 G 0,5	Lapp 0022701	3 G 0,5	6,2	43.0	52
ÖLFLEX ROBUST 215 C 3 X 0,5	Lapp 0022702	3 X 0,5	6,2	43.0	52
ÖLFLEX ROBUST 215 C 4 G 0,5	Lapp 0022703	4 G 0,5	6,6	49.0	59
ÖLFLEX ROBUST 215 C 4 X 0,5	Lapp 0022704	4 X 0,5	6,6	49.0	59
ÖLFLEX ROBUST 215 C 5 G 0,5	Lapp 0022705	5 G 0,5	7,1	57.0	68
ÖLFLEX ROBUST 215 C 5 X 0,5	Lapp 0022706	5 X 0,5	7,1	57.0	68
ÖLFLEX ROBUST 215 C 7 G 0,5	Lapp 0022708	7 G 0,5	7,7	69.0	85
ÖLFLEX ROBUST 215 C 7 X 0,5	Lapp 0022709	7 X 0,5	7,7	69.0	85
ÖLFLEX ROBUST 215 C 12 G 0,5	Lapp 0022711	12 G 0,5	10,1	104.0	136
ÖLFLEX ROBUST 215 C 18 G 0,5	Lapp 0022712	18 G 0,5	11,8	141.0	189
ÖLFLEX ROBUST 215 C 25 G 0,5	Lapp 0022713	25 G 0,5	13,7	211.0	265
ÖLFLEX ROBUST 215 C 2 X 0,75	Lapp 0022717	2 X 0,75	6,3	43.0	50
ÖLFLEX ROBUST 215 C 3 G 0,75	Lapp 0022718	3 G 0,75	6,6	52.0	60
ÖLFLEX ROBUST 215 C 3 X 0,75	Lapp 0022719	3 X 0,75	6,6	52.0	60
ÖLFLEX ROBUST 215 C 4 G 0,75	Lapp 0022720	4 G 0,75	7,1	61.0	72
ÖLFLEX ROBUST 215 C 4 X 0,75	Lapp 0022721	4 X 0,75	7,1	61.0	72
ÖLFLEX ROBUST 215 C 5 G 0,75	Lapp 0022722	5 G 0,75	7,9	72.0	88
ÖLFLEX ROBUST 215 C 5 X 0,75	Lapp 0022723	5 X 0,75	7,9	72.0	88
ÖLFLEX ROBUST 215 C 7 G 0,75	Lapp 0022724	7 G 0,75	8,5	89.0	110
ÖLFLEX ROBUST 215 C 7 X 0,75	Lapp 0022725	7 X 0,75	8,5	89.0	110
ÖLFLEX ROBUST 215 C 12 G 0,75	Lapp 0022727	12 G 0,75	11,1	138.0	177
ÖLFLEX ROBUST 215 C 18 G 0,75	Lapp 0022728	18 G 0,75	13.0	211.0	247
ÖLFLEX ROBUST 215 C 25 G 0,75	Lapp 0022729	25 G 0,75	15,1	280.0	347

ÖLFLEX ROBUST 215 C 7 X 0,75_

Lapp 0022725



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX ROBUST 215 C 34 G 0,75	Lapp 0022730	34 G 0,75	17,5	380.0	460
ÖLFLEX ROBUST 215 C 2 X 1,0	Lapp 0022733	2 X 1,0	6,6	51.0	60
ÖLFLEX ROBUST 215 C 3 G 1,0	Lapp 0022734	3 G 1,0	6,9	62.0	70
ÖLFLEX ROBUST 215 C 3 X 1,0	Lapp 0022735	3 X 1,0	6,9	62.0	70
ÖLFLEX ROBUST 215 C 4 G 1,0	Lapp 0022736	4 G 1,0	7,4	74.0	85
ÖLFLEX ROBUST 215 C 4 X 1,0	Lapp 0022737	4 X 1,0	7,4	74.0	85
ÖLFLEX ROBUST 215 C 5 G 1,0	Lapp 0022738	5 G 1,0	8,3	88.0	103
ÖLFLEX ROBUST 215 C 5 X 1,0	Lapp 0022739	5 X 1,0	8,3	88.0	103
ÖLFLEX ROBUST 215 C 7 G 1,0	Lapp 0022740	7 G 1,0	8,9	112.0	131
ÖLFLEX ROBUST 215 C 12 G 1,0	Lapp 0022742	12 G 1,0	11,7	185.0	213
ÖLFLEX ROBUST 215 C 18 G 1,0	Lapp 0022743	18 G 1,0	14,1	268.0	321
ÖLFLEX ROBUST 215 C 25 G 1,0	Lapp 0022744	25 G 1,0	16,2	354.0	425
ÖLFLEX ROBUST 215 C 2 X 1,5	Lapp 0022748	2 X 1,5	7,2	65.0	71
ÖLFLEX ROBUST 215 C 3 G 1,5	Lapp 0022749	3 G 1,5	7,6	82.0	90
ÖLFLEX ROBUST 215 C 3 X 1,5	Lapp 0022750	3 X 1,5	7,6	82.0	90
ÖLFLEX ROBUST 215 C 4 G 1,5	Lapp 0022751	4 G 1,5	8,4	100.0	114
ÖLFLEX ROBUST 215 C 4 X 1,5	Lapp 0022752	4 X 1,5	8,4	100.0	114
ÖLFLEX ROBUST 215 C 5 G 1,5	Lapp 0022753	5 G 1,5	9,1	119.0	136
ÖLFLEX ROBUST 215 C 5 X 1,5	Lapp 0022754	5 X 1,5	9,1	119.0	136
ÖLFLEX ROBUST 215 C 7 G 1,5	Lapp 0022756	7 G 1,5	10,0	154.0	177
ÖLFLEX ROBUST 215 C 7 X 1,5	Lapp 0022757	7 X 1,5	10,0	154.0	177
ÖLFLEX ROBUST 215 C 12 G 1,5	Lapp 0022760	12 G 1,5	13,4	268.0	290
ÖLFLEX ROBUST 215 C 18 G 1,5	Lapp 0022761	18 G 1,5	15,8	373.0	435
ÖLFLEX ROBUST 215 C 25 G 1,5	Lapp 0022762	25 G 1,5	18,2	530.0	579
ÖLFLEX ROBUST 215 C 34 G 1,5	Lapp 0022763	34 G 1,5	21,2	683.0	797
ÖLFLEX ROBUST 215 C 3 G 2,5	Lapp 0022767	3 G 2,5	9,1	118.0	134

ÖLFLEX ROBUST 215 C 7 X 0,75_

Lapp 0022725



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX ROBUST 215 C 4 G 2,5	Lapp 0022768	4 G 2,5	10,0	147,0	169
ÖLFLEX ROBUST 215 C 5 G 2,5	Lapp 0022769	5 G 2,5	11,1	176,0	207
ÖLFLEX ROBUST 215 C 7 G 2,5	Lapp 0022770	7 G 2,5	12,0	253,0	270
ÖLFLEX ROBUST 215 C 4 G 4	Lapp 0022774	4 G 4	11,9	190,0	258
ÖLFLEX ROBUST 215 C 4 G 6	Lapp 0022776	4 G 6	14,5	290,0	392
ÖLFLEX ROBUST 215 C 4 G 10	Lapp 0022777	4 G 10	17,5	458,0	602
ÖLFLEX ROBUST 215 C 4 G 16	Lapp 0022778	4 G 16	20,2	736,6	928
ÖLFLEX ROBUST 215 C 4 G 25	Lapp 0022771	4 G 25	25,1	1126,7	1411
ÖLFLEX ROBUST 215 C 4 G 35	Lapp 0022780	4 G 35	28,0	1540,0	1883