



Description: ÖLFLEX ROBUST FD C 12 G 1,5_

Lapp code: Lapp 0026725

The **Test voltage** of the cable Lapp 0026725 is 4000 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Particularly in wet areas of machine tools and transfer lines
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Resistant to contact with plant, animal or synthetic-based organic oils, greases, waxes and the related emulsions
- Assembly lines, production lines, in all kinds of machines

Product Make-up

- Extra-fine wire, tinned copper strands
- Core insulation: TPE
- Cores twisted together in extremely short lay lengths
- Non-woven wrapping
- Inner sheath made of TPE
- Tinned-copper braiding
- Robust outer sheath made of special halogen-free TPE, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026725 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® ROBUST FD C | | | | | |
| ÖLFLEX ROBUST FD C 3 G 0,75 | Lapp 0026701 | 3 G 0,75 | 9.1 | 49.6 | 110 |
| ÖLFLEX ROBUST FD C 4 G 0,75 | Lapp 0026702 | 4 G 0,75 | 10.1 | 60.9 | 137 |
| ÖLFLEX ROBUST FD C 5 G 0,75 | Lapp 0026703 | 5 G 0,75 | 10.8 | 72.8 | 160 |
| ÖLFLEX ROBUST FD C 7 G 0,75 | Lapp 0026704 | 7 G 0,75 | 12.6 | 107.2 | 238 |
| ÖLFLEX ROBUST FD C 12 G 0,75 | Lapp 0026705 | 12 G 0,75 | 15.0 | 151.5 | 312 |
| ÖLFLEX ROBUST FD C 18 G 0,75 | Lapp 0026706 | 18 G 0,75 | 17.7 | 205.5 | 448 |
| ÖLFLEX ROBUST FD C 25 G 0,75 | Lapp 0026707 | 25 G 0,75 | 21.7 | 299.1 | 657 |
| ÖLFLEX ROBUST FD C 3 G 1,0 | Lapp 0026709 | 3 G 1,0 | 9.8 | 61.1 | 125 |
| ÖLFLEX ROBUST FD C 7 G 1,0 | Lapp 0026716 | 7 G 1,0 | 13.9 | 132.3 | 278 |
| ÖLFLEX ROBUST FD C 12 G 1,0 | Lapp 0026717 | 12 G 1,0 | 16.1 | 189.1 | 370 |
| ÖLFLEX ROBUST FD C 3 G 1,5 | Lapp 0026721 | 3 G 1,5 | 10.9 | 79.8 | 163 |
| ÖLFLEX ROBUST FD C 4 G 1,5 | Lapp 0026722 | 4 G 1,5 | 12.1 | 99.2 | 210 |
| ÖLFLEX ROBUST FD C 5 G 1,5 | Lapp 0026723 | 5 G 1,5 | 13.6 | 129.7 | 264 |
| ÖLFLEX ROBUST FD C 7 G 1,5 | Lapp 0026724 | 7 G 1,5 | 15.8 | 175.2 | 370 |
| ÖLFLEX ROBUST FD C 12 G 1,5 | Lapp 0026725 | 12 G 1,5 | 18.4 | 257.1 | 498 |
| ÖLFLEX ROBUST FD C 18 G 1,5 | Lapp 0026726 | 18 G 1,5 | 22.1 | 378.9 | 749 |
| ÖLFLEX ROBUST FD C 25 G 1,5 | Lapp 0026727 | 25 G 1,5 | 27.1 | 555.5 | 1042 |
| ÖLFLEX ROBUST FD C 4 G 2,5 | Lapp 0026731 | 4 G 2,5 | 14.4 | 161.5 | 307 |
| ÖLFLEX ROBUST FD C 5 G 2,5 | Lapp 0026732 | 5 G 2,5 | 15.5 | 188.3 | 361 |
| ÖLFLEX ROBUST FD C 7 G 2,5 | Lapp 0026733 | 7 G 2,5 | 18.3 | 252.6 | 512 |
| ÖLFLEX ROBUST FD C 12 G 2,5 | Lapp 0026734 | 12 G 2,5 | 21.9 | 406.5 | 730 |
| ÖLFLEX ROBUST FD C 4 G 4 | Lapp 0026741 | 4 G 4 | 16.2 | 227.3 | 412 |
| ÖLFLEX ROBUST FD C 4 G 6 | Lapp 0026751 | 4 G 6 | 17.2 | 306.7 | 519 |
| ÖLFLEX ROBUST FD C 4 G 10 | Lapp 0026761 | 4 G 10 | 23.3 | 513.6 | 853 |

ÖLFLEX ROBUST FD C 12 G 1,5_

Lapp 0026725



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX ROBUST FD C 4 G 16 | Lapp 0026771 | 4 G 16 | 27.2 | 809.6 | 1273 |