



**Description:** ÖLFLEX SERVO 719 CY 4 G 1,5 + (2 x 1,5)\_

**Lapp code:** Lapp 1020019

The **Test voltage** of the cable Lapp 1020019 is Core/Core: 4 kV Core/Screen: 4 kV.

## Application range

- Connecting cable between servo controller and motor
- For static and occasionally flexible use
- Plant engineering
- Machine tools
- Printing machines

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: polypropylene (PP)
- Individual design depending on the item: power cores with or without one or two individually screened control core pairs twisted together in short lay lengths
- Tinned copper screen braiding
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 1020019 and much more.

CABLE LIST - all informations you need you can find here

| Product Name                                       | Lapp Nr.     | Number of cores and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® SERVO 719 CY                               |              |   |                     |                      |                |
| ÖLFLEX SERVO 719 CY 4 G 1,5                        | Lapp 1020010 | 4 G 1,5   | 8,4                 | 83.0                 | 130            |
| ÖLFLEX SERVO 719 CY 4 G 2,5                        | Lapp 1020011 | 4 G 2,5   | 9,9                 | 125.0                | 190            |
| ÖLFLEX SERVO 719 CY 4 G 4                          | Lapp 1020012 | 4 G 4   | 11,7                | 191.0                | 273            |
| ÖLFLEX SERVO 719 CY 4 G 6                          | Lapp 1020013 | 4 G 6   | 13,7                | 290.0                | 394            |
| ÖLFLEX SERVO 719 CY 4 G 10                         | Lapp 1020014 | 4 G 10  | 16,7                | 452.0                | 581            |
| ÖLFLEX SERVO 719 CY 4 G 16                         | Lapp 1020015 | 4 G 16  | 20,1                | 721.0                | 884            |
| ÖLFLEX SERVO 719 CY 4 G 25                         | Lapp 1020016 | 4 G 25  | 24,3                | 1100.0               | 1348           |
| ÖLFLEX SERVO 719 CY 4 G 35                         | Lapp 1020017 | 4 G 35  | 27,7                | 1548.0               | 1840           |
| ÖLFLEX SERVO 719 CY 4 G 50                         | Lapp 1020018 | 4 G 50  | 33,7                | 2151.0               | 2645           |
| ÖLFLEX SERVO 719 CY 4 G 1,5 + (2 x 1,5)            | Lapp 1020019 | 4 G 1,5 + (2 x 1,5)                               | 11,5                | 146.0                | 242            |
| ÖLFLEX SERVO 719 CY 4 G 2,5 + (2 x 1,5)            | Lapp 1020020 | 4 G 2,5 + (2 x 1,5)                               | 12,9                | 189.0                | 306            |
| ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,5)              | Lapp 1020021 | 4 G 4 + (2 x 1,5)                                 | 15,0                | 271.0                | 420            |
| ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,5)              | Lapp 1020022 | 4 G 6 + (2 x 1,5)                                 | 17,0                | 351.0                | 529            |
| ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,5)             | Lapp 1020023 | 4 G 10 + (2 x 1,5)                                | 19,5                | 540.0                | 752            |
| ÖLFLEX SERVO 719 CY 4 G 0,75 + 2 x (2 x 0,34)      | Lapp 1020024 | 4 G 0,75 + 2 x (2 x 0,34)                         | 9,7                 | 99.0                 | 163            |
| ÖLFLEX SERVO 719 CY 4 G 1,5 + 2 x (2 x 0,75)       | Lapp 1020025 | 4 G 1,5 + 2 x (2 x 0,75)                          | 12,3                | 150.0                | 245            |
| ÖLFLEX SERVO 719 CY 4 G 2,5 + 2 x (2 x 1,0)        | Lapp 1020026 | 4 G 2,5 + 2 x (2 x 1,0)                           | 14,7                | 223.0                | 357            |
| ÖLFLEX SERVO 719 CY 4 G 4 + 2 x (2 x 1,0)          | Lapp 1020027 | 4 G 4 + 2 x (2 x 1,0)                             | 16,4                | 288.0                | 452            |
| ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,0) + (2 x 1,5)  | Lapp 1020028 | 4 G 4 + (2 x 1,0) + (2 x 1,5)                     | 16,6                | 307.0                | 469            |
| ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,0) + (2 x 1,5)  | Lapp 1020029 | 4 G 6 + (2 x 1,0) + (2 x 1,5)                     | 18,5                | 421.0                | 617            |
| ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,0) + (2 x 1,5) | Lapp 1020030 | 4 G 10 + (2 x 1,0) + (2 x 1,5)                    | 22,1                | 588.0                | 852            |
| ÖLFLEX SERVO 719 CY 4 G 16 + 2 x (2 x 1,5)         | Lapp 1020031 | 4 G 16 + 2 x (2 x 1,5)                            | 25,0                | 876.0                | 1162           |

# ÖLFLEX SERVO 719 CY 4 G 1,5 + (2 x 1,5)\_

Lapp 1020019



| Product Name                                     | Lapp Nr.     | Number of cores and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX SERVO 719<br>CY 4 G 25 + 2 x (2 x<br>1,5) | Lapp 1020032 | 4 G 25 + 2 x (2 x 1,5)                            | 28,7                | 1227.0               | 1590           |
| ÖLFLEX SERVO 719<br>CY 4 G 35 + 2 x (2 x<br>1,5) | Lapp 1020033 | 4 G 35 + 2 x (2 x 1,5)                            | 30,6                | 1652.0               | 2023           |
| ÖLFLEX SERVO 719<br>CY 4 G 50 + 2 x (2 x<br>2,5) | Lapp 1020034 | 4 G 50 + 2 x (2 x 2,5)                            | 37.0                | 2264.0               | 2876           |