



**Description:** ÖLFLEX SERVO 719 CY 4 G 16 + 2 x (2 x 1,5)\_

**Lapp code:** Lapp 1020031

The **Test voltage** of the cable Lapp 1020031 is Core/Core: 4 kV Core/Screen: 4 kV.

## Application range

- Connecting cable between servo controller and motor
- For static and occasionally flexible use
- Plant engineering
- Machine tools
- Printing machines

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: polypropylene (PP)
- Individual design depending on the item: power cores with or without one or two individually screened control core pairs twisted together in short lay lengths
- Tinned copper screen braiding
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 1020031 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO 719 CY					
ÖLFLEX SERVO 719 CY 4 G 1,5	Lapp 1020010	4 G 1,5	8,4	83.0	130
ÖLFLEX SERVO 719 CY 4 G 2,5	Lapp 1020011	4 G 2,5	9,9	125.0	190
ÖLFLEX SERVO 719 CY 4 G 4	Lapp 1020012	4 G 4	11,7	191.0	273
ÖLFLEX SERVO 719 CY 4 G 6	Lapp 1020013	4 G 6	13,7	290.0	394
ÖLFLEX SERVO 719 CY 4 G 10	Lapp 1020014	4 G 10	16,7	452.0	581
ÖLFLEX SERVO 719 CY 4 G 16	Lapp 1020015	4 G 16	20,1	721.0	884
ÖLFLEX SERVO 719 CY 4 G 25	Lapp 1020016	4 G 25	24,3	1100.0	1348
ÖLFLEX SERVO 719 CY 4 G 35	Lapp 1020017	4 G 35	27,7	1548.0	1840
ÖLFLEX SERVO 719 CY 4 G 50	Lapp 1020018	4 G 50	33,7	2151.0	2645
ÖLFLEX SERVO 719 CY 4 G 1,5 + (2 x 1,5)	Lapp 1020019	4 G 1,5 + (2 x 1,5)	11,5	146.0	242
ÖLFLEX SERVO 719 CY 4 G 2,5 + (2 x 1,5)	Lapp 1020020	4 G 2,5 + (2 x 1,5)	12,9	189.0	306
ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,5)	Lapp 1020021	4 G 4 + (2 x 1,5)	15,0	271.0	420
ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,5)	Lapp 1020022	4 G 6 + (2 x 1,5)	17,0	351.0	529
ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,5)	Lapp 1020023	4 G 10 + (2 x 1,5)	19,5	540.0	752
ÖLFLEX SERVO 719 CY 4 G 0,75 + 2 x (2 x 0,34)	Lapp 1020024	4 G 0,75 + 2 x (2 x 0,34)	9,7	99.0	163
ÖLFLEX SERVO 719 CY 4 G 1,5 + 2 x (2 x 0,75)	Lapp 1020025	4 G 1,5 + 2 x (2 x 0,75)	12,3	150.0	245
ÖLFLEX SERVO 719 CY 4 G 2,5 + 2 x (2 x 1,0)	Lapp 1020026	4 G 2,5 + 2 x (2 x 1,0)	14,7	223.0	357
ÖLFLEX SERVO 719 CY 4 G 4 + 2 x (2 x 1,0)	Lapp 1020027	4 G 4 + 2 x (2 x 1,0)	16,4	288.0	452
ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,0) + (2 x 1,5)	Lapp 1020028	4 G 4 + (2 x 1,0) + (2 x 1,5)	16,6	307.0	469
ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,0) + (2 x 1,5)	Lapp 1020029	4 G 6 + (2 x 1,0) + (2 x 1,5)	18,5	421.0	617
ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,0) + (2 x 1,5)	Lapp 1020030	4 G 10 + (2 x 1,0) + (2 x 1,5)	22,1	588.0	852
ÖLFLEX SERVO 719 CY 4 G 16 + 2 x (2 x 1,5)	Lapp 1020031	4 G 16 + 2 x (2 x 1,5)	25,0	876.0	1162

# ÖLFLEX SERVO 719 CY 4 G 16 + 2 x (2 x 1,5)\_

Lapp 1020031



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX SERVO 719 CY 4 G 25 + 2 x (2 x 1,5)	Lapp 1020032	4 G 25 + 2 x (2 x 1,5)	28,7	1227.0	1590
ÖLFLEX SERVO 719 CY 4 G 35 + 2 x (2 x 1,5)	Lapp 1020033	4 G 35 + 2 x (2 x 1,5)	30,6	1652.0	2023
ÖLFLEX SERVO 719 CY 4 G 50 + 2 x (2 x 2,5)	Lapp 1020034	4 G 50 + 2 x (2 x 2,5)	37.0	2264.0	2876