



Description: ÖLFLEX SERVO 719 CY 4 G 2,5_

Lapp code: Lapp 1020011

The **Test voltage** of the cable Lapp 1020011 is Core/Core: 4 kV Core/Screen: 4 kV.

Application range

- Connecting cable between servo controller and motor
- For static and occasionally flexible use
- Plant engineering
- Machine tools
- Printing machines

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: polypropylene (PP)
- Individual design depending on the item: power cores with or without one or two individually screened control core pairs twisted together in short lay lengths
- Tinned copper screen braiding
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 1020011 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® SERVO 719 CY | | | | | |
| ÖLFLEX SERVO 719 CY 4 G 1,5 | Lapp 1020010 | 4 G 1,5 | 8,4 | 83.0 | 130 |
| ÖLFLEX SERVO 719 CY 4 G 2,5 | Lapp 1020011 | 4 G 2,5 | 9,9 | 125.0 | 190 |
| ÖLFLEX SERVO 719 CY 4 G 4 | Lapp 1020012 | 4 G 4 | 11,7 | 191.0 | 273 |
| ÖLFLEX SERVO 719 CY 4 G 6 | Lapp 1020013 | 4 G 6 | 13,7 | 290.0 | 394 |
| ÖLFLEX SERVO 719 CY 4 G 10 | Lapp 1020014 | 4 G 10 | 16,7 | 452.0 | 581 |
| ÖLFLEX SERVO 719 CY 4 G 16 | Lapp 1020015 | 4 G 16 | 20,1 | 721.0 | 884 |
| ÖLFLEX SERVO 719 CY 4 G 25 | Lapp 1020016 | 4 G 25 | 24,3 | 1100.0 | 1348 |
| ÖLFLEX SERVO 719 CY 4 G 35 | Lapp 1020017 | 4 G 35 | 27,7 | 1548.0 | 1840 |
| ÖLFLEX SERVO 719 CY 4 G 50 | Lapp 1020018 | 4 G 50 | 33,7 | 2151.0 | 2645 |
| ÖLFLEX SERVO 719 CY 4 G 1,5 + (2 x 1,5) | Lapp 1020019 | 4 G 1,5 + (2 x 1,5) | 11,5 | 146.0 | 242 |
| ÖLFLEX SERVO 719 CY 4 G 2,5 + (2 x 1,5) | Lapp 1020020 | 4 G 2,5 + (2 x 1,5) | 12,9 | 189.0 | 306 |
| ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,5) | Lapp 1020021 | 4 G 4 + (2 x 1,5) | 15,0 | 271.0 | 420 |
| ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,5) | Lapp 1020022 | 4 G 6 + (2 x 1,5) | 17,0 | 351.0 | 529 |
| ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,5) | Lapp 1020023 | 4 G 10 + (2 x 1,5) | 19,5 | 540.0 | 752 |
| ÖLFLEX SERVO 719 CY 4 G 0,75 + 2 x (2 x 0,34) | Lapp 1020024 | 4 G 0,75 + 2 x (2 x 0,34) | 9,7 | 99.0 | 163 |
| ÖLFLEX SERVO 719 CY 4 G 1,5 + 2 x (2 x 0,75) | Lapp 1020025 | 4 G 1,5 + 2 x (2 x 0,75) | 12,3 | 150.0 | 245 |
| ÖLFLEX SERVO 719 CY 4 G 2,5 + 2 x (2 x 1,0) | Lapp 1020026 | 4 G 2,5 + 2 x (2 x 1,0) | 14,7 | 223.0 | 357 |
| ÖLFLEX SERVO 719 CY 4 G 4 + 2 x (2 x 1,0) | Lapp 1020027 | 4 G 4 + 2 x (2 x 1,0) | 16,4 | 288.0 | 452 |
| ÖLFLEX SERVO 719 CY 4 G 4 + (2 x 1,0) + (2 x 1,5) | Lapp 1020028 | 4 G 4 + (2 x 1,0) + (2 x 1,5) | 16,6 | 307.0 | 469 |
| ÖLFLEX SERVO 719 CY 4 G 6 + (2 x 1,0) + (2 x 1,5) | Lapp 1020029 | 4 G 6 + (2 x 1,0) + (2 x 1,5) | 18,5 | 421.0 | 617 |
| ÖLFLEX SERVO 719 CY 4 G 10 + (2 x 1,0) + (2 x 1,5) | Lapp 1020030 | 4 G 10 + (2 x 1,0) + (2 x 1,5) | 22,1 | 588.0 | 852 |
| ÖLFLEX SERVO 719 CY 4 G 16 + 2 x (2 x 1,5) | Lapp 1020031 | 4 G 16 + 2 x (2 x 1,5) | 25,0 | 876.0 | 1162 |

ÖLFLEX SERVO 719 CY 4 G 2,5_

Lapp 1020011



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX SERVO 719 CY 4 G 25 + 2 x (2 x 1,5) | Lapp 1020032 | 4 G 25 + 2 x (2 x 1,5) | 28,7 | 1227.0 | 1590 |
| ÖLFLEX SERVO 719 CY 4 G 35 + 2 x (2 x 1,5) | Lapp 1020033 | 4 G 35 + 2 x (2 x 1,5) | 30,6 | 1652.0 | 2023 |
| ÖLFLEX SERVO 719 CY 4 G 50 + 2 x (2 x 2,5) | Lapp 1020034 | 4 G 50 + 2 x (2 x 2,5) | 37.0 | 2264.0 | 2876 |