



Description: ÖLFLEX SERVO 720 CY 3 x (2 x 0,14) + 2 x (0,5)_

Lapp code: Lapp 0036168

The **Test voltage** of the cable Lapp 0036168 is C/C - C/S 2000 - 1000 V.

Application range

- Analogue and incremental encoders in servo drives
- Servo drives and servo assemblies
- Measurement, control and electrical applications

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Based on PVC
- Refer to "Technical Data" for the colour-codes
- Core and pairs are twisted together
- Tinned copper screen braiding (*with drain wire)
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0036168 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO 720 CY					
ÖLFLEX SERVO 720 CY 4 x 2 x 0,25 + 2 x 1,0 *	Lapp 0036170	4 x 2 x 0,25 + 2 x 1,0 *	8,9	70.8	128
ÖLFLEX SERVO 720 CY 10 x 0,14 + 2 x 0,5	Lapp 0036175	10 x 0,14 + 2 x 0,5	7,9	39.3	88
ÖLFLEX SERVO 720 CY 10 x 0,14 + 4 x 0,5	Lapp 0036177	10 x 0,14 + 4 x 0,5	8.0	51.1	94
ÖLFLEX SERVO 720 CY 15 x 0,14 + 4 x 0,5	Lapp 0036178	15 x 0,14 + 4 x 0,5	8,7	59.7	125
ÖLFLEX SERVO 720 CY 4 x 2 x 0,14 + 4 x 0,5	Lapp 0036181	4 x 2 x 0,14 + 4 x 0,5	8,1	48.8	95
ÖLFLEX SERVO 720 CY 3 x (2 x 0,14) + 2 x (0,5)	Lapp 0036168	3 x (2 x 0,14) + 2 x (0,5)	8,5	67.0	129