Description: ÖLFLEX SERVO 9YSLCY-JB 4 G 6_
Lapp code: Lapp 0037003

The **Test voltage** of the cable Lapp 0037003 is 4000 V.

Application range

- Connecting cable between frequency converter and motor
- In dry, damp or wet interiors
- Paper industry
- Chemical industry
- Heavy industry

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: polypropylene (PP)
- Cores twisted concentrically (symmetrically splitted protective conductor of 3+3 version is gusset-filling divided between the power cores)
- Screening: wrapping of laminated aluminium foil in combination with tinned copper braiding
- 4-core design: transparent PVC outer sheath
- 3+3 core version: PVC outer sheath, black

In our Cable list on next page you can find all interesting information acc. article Lapp 0037003 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO 9YSLCY-JB					
ÖLFLEX SERVO 9YSLCY-JB 4 G 1,5	Lapp 0037000	4 G 1,5	10,5	87.0	230
ÖLFLEX SERVO 9YSLCY-JB 4 G 2,5	Lapp 0037001	4 G 2,5	11,8	133.0	300
ÖLFLEX SERVO 9YSLCY-JB 4 G 4	Lapp 0037002	4 G 4	13,3	213.0	485
ÖLFLEX SERVO 9YSLCY-JB 4 G 6	Lapp 0037003	4 G 6	14,9	298.0	630
ÖLFLEX SERVO 9YSLCY-JB 4 G 10	Lapp 0037004	4 G 10	17,7	460.0	860
ÖLFLEX SERVO 9YSLCY-JB 4 G 16	Lapp 0037005	4 G 16	21,5	707.0	1290
ÖLFLEX SERVO 9YSLCY-JB 4 G 25	Lapp 0037006	4 G 25	26,3	1100.0	1860
ÖLFLEX SERVO 9YSLCY-JB 4 G 35	Lapp 0037007	4 G 35	29,7	1542.0	2610
ÖLFLEX SERVO 9YSLCY-JB 4 G 50	Lapp 0037008	4 G 50	34,1	2206.0	2950
ÖLFLEX SERVO 9YSLCY-JB 4 G 70	Lapp 0037009	4 G 70	40,9	3002.0	3950
ÖLFLEX SERVO 9YSLCY-JB 4 G 95	Lapp 0037010	4 G 95	45,4	4004.0	5300
ÖLFLEX SERVO 9YSLCY-JB 4 G 120	Lapp 0037011	4 G 120	49,8	5108.0	6600
ÖLFLEX SERVO 9YSLCY-JB 4 G 150	Lapp 0037012	4 G 150	56,1	6225.0	7043
ÖLFLEX SERVO 9YSLCY-JB 4 G 185	Lapp 0037013	4 G 185	61,4	7568.0	8384
ÖLFLEX SERVO 9YSLCY-JB 4 G 240	Lapp 0037014	4 G 240	67,9	9940.0	12150
ÖLFLEX SERVO 9YSLCY-JB 3 X 1,5 + 3 G 0,25	Lapp 0037015	3 X 1,5 + 3 G 0,25	11,4	88.0	140
ÖLFLEX SERVO 9YSLCY-JB 3 X 2,5 + 3 G 0,5	Lapp 0037016	3 X 2,5 + 3 G 0,5	12,9	130.0	220
ÖLFLEX SERVO 9YSLCY-JB 3 X 4 + 3 G 0,75	Lapp 0037017	3 X 4 + 3 G 0,75	13,6	224.0	323
ÖLFLEX SERVO 9YSLCY-JB 3 X 6 + 3 G 1,0	Lapp 0037018	3 X 6 + 3 G 1,0	15,2	276.0	420
ÖLFLEX SERVO 9YSLCY-JB 3 X 10 + 3 G 1,5	Lapp 0037019	3 X 10 + 3 G 1,5	17,4	511.0	615
ÖLFLEX SERVO 9YSLCY-JB 3 X 16 + 3 G 2,5	Lapp 0037020	3 X 16 + 3 G 2,5	20.0	751.0	819
ÖLFLEX SERVO 9YSLCY-JB 3 X 25 + 3 G 4	Lapp 0037021	3 X 25 + 3 G 4	24,3	1204.0	1325

PERTRONIC CABLES SASA PERIC ROSENSTR.6 74239 HARDTHAUSEN TEL: 07139-507-8687 FAX: 07139-507-8680
www.pertronic-cables.com | sales@pertronic.eu | Skype PERTRONIC-CABLES | see you GOOGLE + PERTRONIC KABEL

Product Name	Lapp Nr.	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX SERVO 9YSLCY-JB 3 X 35 + 3 G 6	Lapp 0037022	3 X 35 + 3 G 6	27,5	1535.0	1718
ÖLFLEX SERVO 9YSLCY-JB 3 X 50 + 3 G 10	Lapp 0037023	3 X 50 + 3 G 10	31,1	2156.0	2399
ÖLFLEX SERVO 9YSLCY-JB 3 X 70 + 3 G 10	Lapp 0037024	3 X 70 + 3 G 10	37,1	2980.0	3056
ÖLFLEX SERVO 9YSLCY-JB 3 X 95 + 3 G 16	Lapp 0037025	3 X 95 + 3 G 16	40.0	3953.0	4162
ÖLFLEX SERVO 9YSLCY-JB 3 X 120 + 3 G 16	Lapp 0037026	3 X 120 + 3 G 16	42,6	4836.0	5074
ÖLFLEX SERVO 9YSLCY-JB 3 X 150 + 3 G 25	Lapp 0037027	3 X 150 + 3 G 25	50.0	5412.0	6128
ÖLFLEX SERVO 9YSLCY-JB 3 X 185 + 3 G 35	Lapp 0037028	3 X 185 + 3 G 35	55,6	7077.0	7820

PERTRONIC CABLES SASA PERIC ROSENSTR.6 74239 HARDTHAUSEN TEL: 07139-507-8687 FAX: 07139-507-8680
www.pertronic-cables.com | sales@pertronic.eu | Skype PERTRONIC-CABLES | see you GOOGLE + PERTRONIC KABEL