



Description: ÖLFLEX SERVO FD 781 CY 4 G 4_

Lapp code: Lapp 0036322

The **Test voltage** of the cable Lapp 0036322 is 4000 V.

Application range

- Connecting cable between Frequency converter and motor
- For power circuits in machine cabling
- In dry, damp or wet interiors with normal mechanical stress conditions
- Only for outdoor use within the indicated operating temperature range, with UV-protection

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: polypropylene (PP)
- Cores twisted in short lay lengths
- Non-woven wrapping
- Tinned-copper braiding
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 0036322 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO FD 781 CY					
ÖLFLEX SERVO FD 781 CY 4 G 1,5	Lapp 0036320	4 G 1,5	9.8	89.0	157
ÖLFLEX SERVO FD 781 CY 4 G 2,5	Lapp 0036321	4 G 2,5	11.9	133.8	233
ÖLFLEX SERVO FD 781 CY 4 G 4	Lapp 0036322	4 G 4	13.5	210.9	335
ÖLFLEX SERVO FD 781 CY 4 G 10	Lapp 0036324	4 G 10	19.7	488.2	747
ÖLFLEX SERVO FD 781 CY 4 G 16	Lapp 0036325	4 G 16	23.9	744.8	1109
ÖLFLEX SERVO FD 781 CY 4 G 35	Lapp 0036327	4 G 35	33.3	1565.4	2264
ÖLFLEX SERVO FD 781 CY 4 G 50	Lapp 0036328	4 G 50	38.3	2174.9	3090