



Description: ÖLFLEX SF 3 G 0,75_

Lapp code: Lapp 0027591

The **Test voltage** of the cable Lapp 0027591 is 3000 V.

Application range

- Very suitable for domestic appliances, electrical power tools, and various handyman tools
- H05VV-F cable types may not be used in commercial premises, with the exception of offices.
- Not for permanent outdoor use.

Product Make-up

- Super-fine strands of bare copper wire with an individual wire diameter of 0.07 mm
- PVC core insulation, cold-resistant
- PVC outer sheath, cold-resistant, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 0027591 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SF					
ÖLFLEX SF 2 X 0,75	Lapp 0027590	2 X 0,75	6,4	14.9	50
ÖLFLEX SF 3 G 0,75	Lapp 0027591	3 G 0,75	7.0	22.3	60
ÖLFLEX SF 4 G 0,75	Lapp 00275923	4 G 0,75	7,7	29.7	73
ÖLFLEX SF 5 G 0,75	Lapp 00275933	5 G 0,75	8,7	37.1	88
ÖLFLEX SF 7 G 0,75	Lapp 0027594	7 G 0,75	10,4	51.5	109
ÖLFLEX SF 2 X 1,0	Lapp 0027600	2 X 1,0	6,8	20.1	74
ÖLFLEX SF 3 G 1,0	Lapp 0027601	3 G 1,0	7,4	30.2	87
ÖLFLEX SF 5 G 1,0	Lapp 00276033	5 G 1,0	9,2	50.8	130
ÖLFLEX SF 3 G 1,5	Lapp 0027701	3 G 1,5	8,7	44.8	116
ÖLFLEX SF 4 G 1,5	Lapp 00277023	4 G 1,5	9,9	61.0	166
ÖLFLEX SF 5 G 1,5	Lapp 00277033	5 G 1,5	11,1	72.0	184