



Description: ÖLFLEX SMART 108 4 G0,5_

Lapp code: Lapp 10040099

The **Test voltage** of the cable Lapp 10040099 is 4000 V.

Application range

- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Dry or damp rooms that are subject to medium mechanical loads
- Main dimensions available, further dimensions see ÖLFLEX® CLASSIC 110
- For extended applications and individual lengths, see ÖLFLEX® CLASSIC 110

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation, T12
- Two-layer PVC outer sheath, TM2; outside silvergrey

In our Cable list on next page you can find all interesting information acc. article Lapp 10040099 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX SMART 108 2 X0,5 | Lapp 17520099 | 2 X0,5 | 4,8 | 9.6 | 35 |
| ÖLFLEX SMART 108 3 G0,5 | Lapp 10030099 | 3 G0,5 | 5,1 | 14.4 | 42 |
| ÖLFLEX SMART 108 3 X0,5 | Lapp 17530099 | 3 X0,5 | 5,1 | 14.4 | 42 |
| ÖLFLEX SMART 108 4 G0,5 | Lapp 10040099 | 4 G0,5 | 5,7 | 19.2 | 54 |
| ÖLFLEX SMART 108 4 X0,5 | Lapp 17540099 | 4 X0,5 | 5,7 | 19.2 | 54 |
| ÖLFLEX SMART 108 5 G0,5 | Lapp 10050099 | 5 G0,5 | 6,2 | 24.0 | 63 |
| ÖLFLEX SMART 108 7 G0,5 | Lapp 10070099 | 7 G0,5 | 6,7 | 33.6 | 81 |
| ÖLFLEX SMART 108 2 X0,75 | Lapp 18020099 | 2 X0,75 | 5,4 | 14.4 | 45 |
| ÖLFLEX SMART 108 3 G0,75 | Lapp 11030099 | 3 G0,75 | 5,7 | 21.6 | 55 |
| ÖLFLEX SMART 108 3 X0,75 | Lapp 18030099 | 3 X0,75 | 5,7 | 21.6 | 55 |
| ÖLFLEX SMART 108 4 G0,75 | Lapp 11040099 | 4 G0,75 | 6,2 | 28.8 | 66 |
| ÖLFLEX SMART 108 4 X0,75 | Lapp 18040099 | 4 X0,75 | 6,2 | 28.8 | 66 |
| ÖLFLEX SMART 108 5 G0,75 | Lapp 11050099 | 5 G0,75 | 6,7 | 36.0 | 79 |
| ÖLFLEX SMART 108 7 G0,75 | Lapp 11070099 | 7 G0,75 | 7,3 | 50.0 | 101 |
| ÖLFLEX SMART 108 2 X1,0 | Lapp 18520099 | 2 X1,0 | 5,7 | 19.2 | 53 |
| ÖLFLEX SMART 108 3 G1,0 | Lapp 12030099 | 3 G1,0 | 6.0 | 28.8 | 65 |
| ÖLFLEX SMART 108 4 G1,0 | Lapp 12040099 | 4 G1,0 | 6,5 | 38.4 | 79 |
| ÖLFLEX SMART 108 5 G1,0 | Lapp 12050099 | 5 G1,0 | 7,1 | 48.0 | 94 |
| ÖLFLEX SMART 108 7 G1,0 | Lapp 12070099 | 7 G1,0 | 8.0 | 67.0 | 126 |
| ÖLFLEX SMART 108 2 X1,5 | Lapp 19020099 | 2 X1,5 | 6,3 | 29.0 | 68 |
| ÖLFLEX SMART 108 3 G1,5 | Lapp 13030099 | 3 G1,5 | 6,7 | 43.0 | 84 |
| ÖLFLEX SMART 108 4 G1,5 | Lapp 13040099 | 4 G1,5 | 7,2 | 58.0 | 104 |
| ÖLFLEX SMART 108 5 G1,5 | Lapp 13050099 | 5 G1,5 | 8,1 | 72.0 | 128 |
| ÖLFLEX SMART 108 7 G1,5 | Lapp 13070099 | 7 G1,5 | 8,9 | 101.0 | 166 |
| ÖLFLEX SMART 108 2 X2,5 | Lapp 19520099 | 2 X2,5 | 7,5 | 48.0 | 101 |

ÖLFLEX SMART 108 4 G0,5_

Lapp 10040099



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX SMART 108 3 G2,5 | Lapp 14030099 | 3 G2,5 | 8,1 | 72.0 | 132 |
| ÖLFLEX SMART 108 4 G2,5 | Lapp 14040099 | 4 G2,5 | 8,9 | 96.0 | 163 |
| ÖLFLEX SMART 108 5 G2,5 | Lapp 14050099 | 5 G2,5 | 10.0 | 120.0 | 200 |
| ÖLFLEX SMART 108 7 G2,5 | Lapp 14070099 | 7 G2,5 | 11,1 | 168.0 | 267 |