



**Description:** ÖLFLEX SOLAR XLS-R T 2 X 2,5\_

**Lapp code:** Lapp 0023983

The **Test voltage** of the cable Lapp 0023983 is AC 6500 V.

## Application range

- Ideal for stand-alone PV power systems
- Gable and flat roof photovoltaic systems
- Photovoltaic plants and solar parks
- Flexible or building-integrated PV systems

## Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation made of electron beam cross-linked copolymer
- Outer sheath made of electron beam cross-linked copolymer
- Outer sheath colour: black
- Cores connected in parallel with a separating strip

In our Cable list on next page you can find all interesting information acc. article Lapp 0023983 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer dimensions/ width x height (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SOLAR XLS-R TCore insulation: red / black					
ÖLFLEX SOLAR XLS-R T 2 X 2,5	Lapp 0023982	2 X 2,5	9,9 x 4,8	48.0	94
ÖLFLEX SOLAR XLS-R T 2 X 4	Lapp 0023984	2 X 4	10,7 x 5,2	76.8	128
ÖLFLEX SOLAR XLS-R T 2 X 6	Lapp 0023986	2 X 6	11,9 x 5,8	115.2	174
ÖLFLEX SOLAR XLS-R T 2 X 10	Lapp 0023988	2 X 10	14,3 x 7	192.0	267
Core insulation: red / blue					
ÖLFLEX SOLAR XLS-R T 2 X 2,5	Lapp 0023983	2 X 2,5	9,9 x 4,8	48.0	94
ÖLFLEX SOLAR XLS-R T 2 X 4	Lapp 0023985	2 X 4	10,7 x 5,2	76.8	128
ÖLFLEX SOLAR XLS-R T 2 X 6	Lapp 0023987	2 X 6	11,9 x 5,8	115.2	174
ÖLFLEX SOLAR XLS-R T 2 X 10	Lapp 0023989	2 X 10	14,3 x 7	192.0	267