



**Description:** ÖLFLEX STATIC CY black 50\_

**Lapp code:** Lapp 4600026

The **Test voltage** of the cable Lapp 4600026 is Core/screen: 2000 V.

## Application range

- Very suitable for power circuits as an external connection or for the internal wirings in electric and electronic equipment
- In dry or damp interiors with low mechanical stress conditions
- Can be used indoors as a connecting cable to the inverter in the photovoltaic sector
- Outdoor use is possible within the indicated operating temperature range

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Based on PVC
- Nonwoven wrapping/plastic foil
- Tinned-copper braiding
- PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 4600026 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm <sup>2</sup> )	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX STATIC CY black 16	Lapp 4600023	16	10,3	177.0	275
ÖLFLEX STATIC CY black 25	Lapp 4600024	25	12,7	267.0	396
ÖLFLEX STATIC CY black 35	Lapp 4600025	35	14,3	384.0	542
ÖLFLEX STATIC CY black 50	Lapp 4600026	50	16,9	537.0	752
ÖLFLEX STATIC CY black 70	Lapp 4600027	70	18,7	763.0	1004
ÖLFLEX STATIC CY black 95	Lapp 4600028	95	21,7	1012.0	1368
ÖLFLEX STATIC CY black 120	Lapp 4600029	120	24,7	1264.0	1719