



Description: ÖLFLEX TRAFO XLv 1.8-3 kV 95_

Lapp code: Lapp 1151010

The **Test voltage** of the cable Lapp 1151010 is AC 6500 V.

Application range

- Required rated voltage 1.8/3 kV
- In the field of renewable energy and conventional power generation
- Photovoltaic plants and solar parks
- Drip-loop installation in wind turbines
- As connection between the converter and the transformer substation

Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation made of cross-linked polyolefin
- Outer sheath made of cross-linked copolymer
- Core insulation and outer sheath are extruded together
- Outer sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 1151010 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® TRAFO XLv 1.8/3 kV					
ÖLFLEX TRAFO XLv 1.8/3 kV 95	Lapp 1151010	95	22.1	912.0	1218
ÖLFLEX TRAFO XLv 1.8/3 kV 120	Lapp 1151011	120	24.4	1152.0	1496
ÖLFLEX TRAFO XLv 1.8/3 kV 150	Lapp 1151012	150	25.9	1440.0	1810
ÖLFLEX TRAFO XLv 1.8/3 kV 185	Lapp 1151013	185	28.2	1776.0	2184
ÖLFLEX TRAFO XLv 1.8/3 kV 240	Lapp 1151014	240	30.3	2304.0	2757
ÖLFLEX TRAFO XLv 1.8/3 kV 300	Lapp 1151015	300	34.0	2880.0	3407