



Description: ÖLFLEX TRUCK 170 TWIN PVC-PVC 2 x 10,0_

Lapp code: Lapp 7027056

The **Test voltage** of the cable Lapp 7027056 is 3000 V AC.

Application range

- Battery cable between the power source and the end user
- Commercial vehicles

Product Make-up

- Strands of bare copper wires
- Core insulation: Based on PVC
- Special PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 7027056 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer dimensions/ width x height (mm)	Copper index (kg/km)
ÖLFLEX® TRUCK 170 TWIN PVC/PVC				
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 6,0	Lapp 7027055	PVC/PVC 2 x 6,0	15,2 x 7,1	115.2
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 10,0	Lapp 7027056	PVC/PVC 2 x 10,0	18,8 x 8,9	192.0
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 16,0	Lapp 7027057	PVC/PVC 2 x 16,0	21 x 10	307.2
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 25,0	Lapp 7027058	PVC/PVC 2 x 25,0	25,6 x 12,3	480.0
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 35,0	Lapp 7027059	PVC/PVC 2 x 35,0	28,4 x 13,5	672.0
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 50,0	Lapp 7027054	PVC/PVC 2 x 50,0	33 x 16	960.0
ÖLFLEX TRUCK 170 TWIN PVC/PVC 2 x 70,0	Lapp 7027052	PVC/PVC 2 x 70,0	39,8 x 18,4	1344.0